



DIMENSIONS



| | |
|-----------|--------------------------------|
| Name | FIFTY H0 RECESSED 120 4000K NT |
| Reference | A2910212NT |
| Color | Textured black |
| RAL | 9005 |
| Category | CEILING RECESSED |

PRODUCT

FIFTY H0 RECESSED 120 4000K NT
 A2910212NT
 Textured black
 9005
 CEILING RECESSED

| | |
|-----------------------------|---------------------------|
| Light source | LED |
| Gross luminous flux | 4400 Lm |
| Power | 30,8 W |
| Power values of the system | 35,81 W |
| Colour temperature | 4000 K |
| Colour Rendering Index | CRI>90 |
| Chromatic stability | Mac Adam Step 2 |
| Light beam angle | 102° |
| Lighting efficiency | 70% |
| Efficacy | 143 Lm/W |
| Current intensity | 900 mA |
| Control through bluetooth | Please Consult |
| Driver | Included |
| Electrical insulation class | ⊕ |
| Voltage | 220 V/240 V |
| Frequency | 50/60 Hz |
| Energy efficiency | A+ |
| LED lifespan | L80B10 (Tc=80°C) >60.000h |

LIGHTING INFORMATION

LED
 4400 Lm
 30,8 W
 35,81 W
 4000 K
 CRI>90
 Mac Adam Step 2
 102°
 70%
 143 Lm/W
 900 mA
 Please Consult
 Included
 ⊕
 220 V/240 V
 50/60 Hz
 A+
 L80B10 (Tc=80°C) >60.000h

| | |
|----------------------|---------------------------|
| Ingress Protection | IP20 |
| Recess measurements | 1148 × 58 mm. |
| Diffuser included | Yes |
| Weight | 4730 g. |
| Packaged weight | 6440 g. |
| Packaging dimensions | Ø168 × 1305 mm. |
| Units per package | 1 |
| Materials | Aluminium / Polycarbonate |

OTHER DATA

IP20
 1148 × 58 mm.
 Yes
 4730 g.
 6440 g.
 Ø168 × 1305 mm.
 1
 Aluminium / Polycarbonate



Fifty is the recessed LED profile of Arkoslight. Fifty, also available in trimless version, it's ideal for longitudinal lighting solutions, where its diffuser contributes to light up in a functional way. On the whole, this profile is capable of assuming the task of highlighting the different lines, volumes or lanes which are defined in the architecture of spaces.

POLAR DIAGRAM



CONICAL DIAGRAM

