


DIMENSIONS



Name	FIFTY H0 RECESSED 300 3000K NT
Reference	A2910411NT
Color	Textured black
RAL	9005
Category	CEILING RECESSED

PRODUCT

FIFTY H0 RECESSED 300 3000K NT
A2910411NT
Textured black
9005
CEILING RECESSED

Light source	LED
Gross luminous flux	10750 Lm
Power	77 W
Power values of the system	89,53 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	102°
Lighting efficiency	70%
Efficacy	140 Lm/W
Current intensity	900 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	⊕
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h

LIGHTING INFORMATION

Ingress Protection	IP20
Recess measurements	2852 × 58 mm.
Diffuser included	Yes
Weight	11830 g.
Packaged weight	16230 g.
Packaging dimensions	Ø168 × 3005 mm.
Units per package	1
Materials	Aluminium / Polycarbonate


OTHER DATA

IP20
2852 × 58 mm.
Yes
11830 g.
16230 g.
Ø168 × 3005 mm.
1
Aluminium / Polycarbonate



Fifty is the recessed LED profile of Arkoslight. Fifty, also available in trimless version, it's ideal for longitudinal lighting solutions, where its diffuser contributes to light up in a functional way. On the whole, this profile is capable of assuming the task of highlighting the different lines, volumes or lanes which are defined in the architecture of spaces.

POLAR DIAGRAM



CONICAL DIAGRAM

