



BUDDY

PURPOSEFUL DESIGN

ARKOSLIGHT



Compatto e performante

Innovativa tecnologia LED all'avanguardia estremamente efficiente. Capace di fornire un'efficacia luminosa fino a **200lm/W**.

Buddy incarna l'eleganza del downlight con il suo design attentamente elaborato e le sue finiture di alta qualità. Il corpo compatto in alluminio e le lenti precise canalizzano tutto il potenziale di questa **nuova generazione di LED**.

Sono disponibili molteplici flussi e potenze, tra cui spiccano **4W** per **800lm** e **11,5W** per **2120lm**.

Un Buddy, molteplici opzioni

Dispone di due modalità di installazione: con una **cornice leggera**, per un'installazione rapida ed efficace; o **senza cornice** (trimless), per un'installazione completamente integrata nell'architettura.

Inoltre, offre due varianti aggiuntive: **fissa** o **basculante**. Estremamente funzionale, la sua versione Tilt è completamente orientabile. Grazie alla possibilità di inclinazione e rotazione, una volta installato, possiamo, con una semplice regolazione manuale, cambiare il suo orientamento.

Disponibile in diverse finiture.



A modern interior space with a large glass wall and a swimming pool. A woman in a black outfit stands by the glass wall, looking out. The room has a minimalist design with white walls and a light-colored floor. A small table with a glass bowl and a framed picture is visible on the left. The ceiling has recessed lights. The glass wall reflects the interior and the pool. The pool is a bright blue color. The background shows a dark sky with some trees.

Stagno e resistente

Grazie al suo elevato grado di **protezione IP54**, anche nella sua versione orientabile Tilt, Buddy è straordinariamente resistente alla penetrazione di particelle di polvere e acqua.




Libertà di scenografie

La famiglia Buddy offre una versatilità eccezionale con tre opzioni di apertura del fascio luminoso: **Spot** / **Medium** / **Flood** / oltre a una versione **Super Spot 12° / 13°**.


Ciò lo rende un downlight versatile, ideale per soddisfare sia le esigenze di illuminazione generale che di accentuazione. Inoltre, Buddy è altamente tecnico.

Grazie al suo LED, lenti di alta qualità e schermo antiabbagliante, è in grado di garantire un flusso luminoso uniforme e livelli bassi di abbagliamento (glare), garantendo un'esperienza di illuminazione ottimale in qualsiasi ambiente.

BUDDY / BUDDY L




BUDDY / BUDDY L TUNABLE WHITE



Buddy Super Spot

Apertura del fascio luminoso estremamente controllata (12° / 13°).
Pensato per essere utilizzato come luce d'accento, Buddy
Super Spot mantiene anche un flusso luminoso uniforme e un
confort visivo ottimale.



Buddy Wall Washer

La virtù del Buddy wall washer risiede nel suo sistema ottico che, come alternativa alla proiezione asimmetrica del faretto orientabile incassato, permette una distribuzione della luce verticale uniforme, senza interruzioni né variazioni di intensità. Disponibile nelle versioni recessed e trimless, con tecnologia 'Tunable White', che consente di regolare sia l'intensità che la temperatura colore.



Buddy Surface

Buddy è disponibile come apparecchio a plafone, distinguendosi per le sue dimensioni ridotte e permettendo l'installazione su qualsiasi tipo di materiale. Una famiglia che ha tutto, progettata da Rubén Saldaña.






100%flux - 3000K



50%flux - 2400K



20%flux - 1800K

DIM to warm

Per i momenti della giornata in cui si cerca l'attivazione e i bioritmi elevati, la luce fredda e abbondante è adatta. Al contrario, nelle ore in cui si cerca la disattivazione e il relax, la temperatura calda e la luce strettamente necessaria sono le caratteristiche desiderate.

Tunable white


Buddy Tunable White consente di regolare in maniera indipendente la temperatura colore e l'intensità della luce, consentendo una flessibilità totale e la riproduzione della luce naturale durante il corso della giornata. Questa tecnologia contribuisce al comfort e al benessere psicologico delle persone.



BUDDY
SPECIFICHE
TECNICHE



VERSIONI



BUDDY



BUDDY TRIMLESS



BUDDY TILT



BUDDY TILT TRIMLESS



BUDDY WALL WASHER




BUDDY WALL WASHER TRIMLESS



BUDDY L



BUDDY L TRIMLESS



BUDDY L TILT



BUDDY L TILT TRIMLESS



BUDDY L



BUDDY L TRIMLESS

FINITURE



W



W



W



W



N




N



N




N



WG



G



WN



NG



WN

FINITURE



WTW



WT



NT



WTG



NTG



BUDDY

									CCT	Beam	LOR
BUDDY	A507-00-	○ -0-	W N WG NG WN						2700K	29° / 43° / 54°	○
	A507-00-	○ -1-	W N WG NG WN						3000K	29° / 43° / 54°	○
	A507-00-	○ -3-	W N WG NG WN						3500K	29° / 43° / 54°	○
	A507-00-	○ -2-	W N WG NG WN						4000K	29° / 43° / 54°	○

III

IP54

CRI>90

L80B10
>66,000h

MacAdam
Step 2

EXCL*

Ø79

UGR <19

									CCT	Beam	LOR
BUDDY Super Spot	A507-00-00-	W N WG NG WN							2700K	12°	62%
	A507-00-01-	W N WG NG WN							3000K	12°	62%
	A507-00-03-	W N WG NG WN							3500K	12°	62%
	A507-00-02-	W N WG NG WN							4000K	12°	62%

III

IP54

CRI>90

L80B10
>55,000h

MacAdam
Step 2

EXCL*

Ø79

UGR <19

									CCT	Beam	LOR
BUDDY Tunable White	A507-01-17-	W N WG NG WN							1800-4000K	28°	85%
	A507-01-18-	W N WG NG WN							2700-5000K	28°	85%
	A507-01-27-	W N WG NG WN							1800-4000K	43°	86%
	A507-01-28-	W N WG NG WN							2700-5000K	43°	86%
	A507-01-37-	W N WG NG WN							1800-4000K	55°	81%
	A507-01-38-	W N WG NG WN							2700-5000K	55°	81%

III

IP54

CRI>90

L80B10
>55,000h

MacAdam
Step 3

EXCL*

Ø79

UGR <19

BUDDY DIM to warm	A507-02-39-	W N WG NG WN							1800-3000K	54°	75%
----------------------	-------------	----------------------	--	--	--	--	--	--	------------	-----	-----

III

IP54

CRI>90

L80B10
>55,000h

MacAdam
Step 3

EXCL*

Ø79

UGR <19


○	BEAM	LOR
1	29°	82%
2	43°	83%
3	54°	80%

OPTIONAL ACCESSORY

BUDDY

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | W | N | WG | NG | WN | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT OPTIONS PLEASE CONSULT



BUDDY Trimless

		CCT	Beam	LOR
BUDDY Trimless	A507-10- -0- W N G	2700K	29° / 43° / 54°	
	A507-10- -1- W N G	3000K	29° / 43° / 54°	
	A507-10- -3- W N G	3500K	29° / 43° / 54°	
	A507-10- -2- W N G	4000K	29° / 43° / 54°	

III

IP54

CRI>90

L80B10
> 66.000 h

MacAdam
Step 2

EXCL*

EXCL**

Ø79

UGR <19

		CCT	Beam	LOR
BUDDY Trimless Super Spot	A507-10-00- W N G	2700K	12°	62%
	A507-10-01- W N G	3000K	12°	62%
	A507-10-03- W N G	3500K	12°	62%
	A507-10-02- W N G	4000K	12°	62%

III

IP54

CRI>90

L80B10
> 55.000 h

MacAdam
Step 2

EXCL*

EXCL**

Ø79

UGR <19

		CCT	Beam	LOR
BUDDY Trimless Tunable White	A507-11-17- W N G	1800-4000K	28°	85%
	A507-11-18- W N G	2700-5000K	28°	85%
	A507-11-27- W N G	1800-4000K	43°	86%
	A507-11-28- W N G	2700-5000K	43°	86%
	A507-11-37- W N G	1800-4000K	55°	81%
	A507-11-38- W N G	2700-5000K	55°	81%

III

IP54

CRI>90

L80B10
> 55.000 h

MacAdam
Step 3

EXCL*

EXCL**

Ø79

UGR <19

		CCT	Beam	LOR
BUDDY Trimless DIM to warm	A507-12-39- W N G	1800-3000K	54°	75%

III

IP54

CRI>90

L80B10
> 55.000 h

MacAdam
Step 3

EXCL*

EXCL**

Ø79

UGR <19

	BEAM	LOR
1	29°	82%
2	43°	83%
3	54°	80%

ACCESSORY



BUDDY Trimless Accessory**

A507-10-90

MANDATORY FOR INSTALLATION

20

Ø79



OPTIONAL ACCESSORIES


BUDDY Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm

A478-00-05



COLOUR | W | N | G | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT OPTIONS PLEASE CONSULT



BUDDY Tilt

									CCT	Beam	LOR
BUDDY Tilt	A508-00-	○ -0-	W	N	WG	NG	WN		2700K	29° / 43° / 54°	○
	A508-00-	○ -1-	W	N	WG	NG	WN		3000K	29° / 43° / 54°	○
	A508-00-	○ -3-	W	N	WG	NG	WN		3500K	29° / 43° / 54°	○
	A508-00-	○ -2-	W	N	WG	NG	WN		4000K	29° / 43° / 54°	○

III

IP54

CRI>90

L80B10
> 66.000h

MacAdam
Step 2

EXCL*

355°

25°

Ø79

									CCT	Beam	LOR
BUDDY Tilt Super Spot	A508-00-00-		W	N	WG	NG	WN		2700K	12°	62%
	A508-00-01-		W	N	WG	NG	WN		3000K	12°	62%
	A508-00-03-		W	N	WG	NG	WN		3500K	12°	62%
	A508-00-02-		W	N	WG	NG	WN		4000K	12°	62%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 2

EXCL*

355°

25°

Ø79

									CCT	Beam	LOR
BUDDY Tilt Tunable White	A508-01-17-		W	N	WG	NG	WN		1800-4000K	28°	85%
	A508-01-18-		W	N	WG	NG	WN		2700-5000K	28°	85%
	A508-01-27-		W	N	WG	NG	WN		1800-4000K	43°	86%
	A508-01-28-		W	N	WG	NG	WN		2700-5000K	43°	86%
	A508-01-37-		W	N	WG	NG	WN		1800-4000K	55°	81%
	A508-01-38-		W	N	WG	NG	WN		2700-5000K	55°	81%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 3

EXCL*

355°

25°

Ø79

									CCT	Beam	LOR
BUDDY Tilt DIM to warm	A508-02-39-		W	N	WG	NG	WN		1800-3000K	54°	75%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 3

EXCL*

355°

25°

Ø79


○	BEAM	LOR
1	29°	82%
2	43°	83%
3	54°	80%

OPTIONAL ACCESSORY

BUDDY Tilt

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE
LIGHTING PARAMETERS



COLOUR | W | N | WG | NG | WN | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT OPTIONS PLEASE CONSULT



BUDDY Tilt Trimless

		CCT	Beam	LOR
BUDDY Tilt Trimless	A508-10- ○ -0- W N G	2700K	29° / 43° / 54°	○
	A508-10- ○ -1- W N G	3000K	29° / 43° / 54°	○
	A508-10- ○ -3- W N G	3500K	29° / 43° / 54°	○
	A508-10- ○ -2- W N G	4000K	29° / 43° / 54°	○

III

IP54

CRI>90

L80B10
> 66.000h

MacAdam
Step 2

EXCL*

EXCL**

25°

Ø79

		CCT	Beam	LOR
BUDDY Tilt Trimless Super Spot	A508-10-00- W N G	2700K	12°	62%
	A508-10-01- W N G	3000K	12°	62%
	A508-10-03- W N G	3500K	12°	62%
	A508-10-02- W N G	4000K	12°	62%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 2

EXCL*

EXCL**

25°

Ø79

		CCT	Beam	LOR
BUDDY Tilt Trimless Tunable White	A508-11-17- W N G	1800-4000K	28°	85%
	A508-11-18- W N G	2700-5000K	28°	85%
	A508-11-27- W N G	1800-4000K	43°	86%
	A508-11-28- W N G	2700-5000K	43°	86%
	A508-11-37- W N G	1800-4000K	55°	81%
	A508-11-38- W N G	2700-5000K	55°	81%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 3

EXCL*

EXCL**

25°

Ø79

		CCT	Beam	LOR
BUDDY Tilt Trimless DIM to warm	A508-12-39- W N G	1800-3000K	54°	75%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 3

EXCL*

EXCL**

25°

Ø79

○	BEAM	LOR
1	29°	82%
2	43°	83%
3	54°	80%

ACCESSORY

BUDDY Tilt Trimless Accessory**

A508-10-90

MANDATORY FOR INSTALLATION




Ø79

OPTIONAL ACCESSORIES

BUDDY Tilt Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR |

W

 |

N

 |

G

 | MATERIAL |

AL

 |

PC/PMMA

 |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT OPTIONS PLEASE CONSULT



BUDDY Wall Washer

					CCT	LOR
BUDDY Wall Washer	A509-00-10-	W	N	WN	2700K	48%
	A509-00-11-	W	N	WN	3000K	48%
	A509-00-13-	W	N	WN	3500K	48%
	A509-00-12-	W	N	WN	4000K	48%

III

IP20

CRI>90

L80B10
>66,000h

MacAdam Step 2

EXCL*

360°

Ø79

					CCT	LOR
BUDDY Wall Washer Tunable White	A509-01-17-	W	N	WN	1800-4000K	49%
	A509-01-18-	W	N	WN	2700-5000K	49%

III

IP20

CRI>90

L80B10
>55,000h

MacAdam Step 3

EXCL*

360°


Ø79

OPTIONAL ACCESSORY

BUDDY Wall Washer

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS



COLOUR | W ☐ | N ☒ | WN ☐ | MATERIAL | AL ☒ | PC/PMMA ☐

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT & DIM OPTIONS PLEASE CONSULT



BUDDY Wall Washer Trimless

				CCT	LOR
BUDDY Wall Washer Trimless	A509-10-10-	W	N	2700K	48%
	A509-10-11-	W	N	3000K	48%
	A509-10-13-	W	N	3500K	48%
	A509-10-12-	W	N	4000K	48%

III

IP20

CRI>90

L80B10
>66,000h

MacAdam Step 2

EXCL*

EXCL**

Ø79

				CCT	LOR
BUDDY Wall Washer Trimless Tunable White	A509-11-17-	W	N	1800-4000K	49%
	A509-11-18-	W	N	2700-5000K	49%

III

IP20

CRI>90

L80B10
>55,000h

MacAdam Step 3

EXCL*

EXCL**

Ø79



ACCESSORY

BUDDY Wall Washer

Trimless Accessory**

A509-10-90

MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES



BUDDY Tilt Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D79 X D120mm












A478-00-05



COLOUR | W □ | N ■ | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS
OTHER CCT & DIM OPTIONS PLEASE CONSULT

BUDDY DRIVERS

DRIVER OPTIONS				P	I	CCT	Flux			
BUDDY 1 Buddy Buddy Trimless Buddy Tilt Buddy Tilt Trimless		 NO DIM	0434-01-85	4 W	125 mA	2700K	760 lm			
						3000K	790 lm			
						3500K	795 lm			
						4000K	800 lm			
BUDDY 2 Buddy Buddy Trimless Buddy Tilt Buddy Tilt Trimless Buddy Wall Washer Buddy Wall Washer Trimless		 NO DIM	0434-01-86	6,6 W	200 mA					
		 DALI	0434-01-89			2700K	1150 lm			
						3000K	1200 lm			
		 CASAMBI	0434-01-91			3500K	1210 lm			
						4000K	1220 lm			
		 PHASE CUT	0434-01-92							
	BUDDY Super Spot		 NO DIM			0434-01-87	6 W	500 mA	2700K	750 lm
									3000K	790 lm
3500K				825 lm						
4000K				845 lm						
BUDDY Tunable White		 DALI	0434-01-90	6,7 W	400 mA	1800-4000K	690 lm			
						2700-5000K	815 lm			
BUDDY DIM to warm		 DALI	0434-01-94	6 W	350 mA	1800-3000K	650 lm			
BUDDY Wall Washer Tunable White		 PHASE CUT	0434-01-95							
BUDDY Wall Washer Tunable White		 DALI	0434-01-96	8,4 W	500 mA	1800-4000K	830 lm			
						2700-5000K	1000 lm			

220
240 V~ | 48V PLEASE CONSULT



BUDDY L

		CCT			Beam			LOR		
BUDDY L	A568-00- ○ -0-	W	N	WG	NG	WN		2700K	32° / 44° / 51°	○
	A568-00- ○ -1-	W	N	WG	NG	WN		3000K	32° / 44° / 51°	○
	A568-00- ○ -3-	W	N	WG	NG	WN		3500K	32° / 44° / 51°	○
	A568-00- ○ -2-	W	N	WG	NG	WN		4000K	32° / 44° / 51°	○
BUDDY L Super Spot	A568-00-00-	W	N	WG	NG	WN		2700K	13°	67%
	A568-00-01-	W	N	WG	NG	WN		3000K	13°	67%
	A568-00-03-	W	N	WG	NG	WN		3500K	13°	67%
	A568-00-02-	W	N	WG	NG	WN		4000K	13°	67%

III

IP54

CRI>90

L80B10
> 66.000 h

MacAdam
Step 2

EXCL*

Ø105

UGR <19

		CCT			Beam			LOR		
BUDDY L Tunable White	A568-01-17-	W	N	WG	NG	WN		1800-4000K	29°	78%
	A568-01-18-	W	N	WG	NG	WN		2700-5000K	29°	78%
	A568-01-27-	W	N	WG	NG	WN		1800-4000K	41°	83%
	A568-01-28-	W	N	WG	NG	WN		2700-5000K	41°	83%
	A568-01-37-	W	N	WG	NG	WN		1800-4000K	51°	84%
	A568-01-38-	W	N	WG	NG	WN		2700-5000K	51°	84%
BUDDY L DIM to warm	A568-02-39-	W	N	WG	NG	WN		1800-3000K	56°	82%

III

IP54

CRI>90

L80B10
> 55.000 h

MacAdam
Step 3

EXCL*

Ø105

UGR <19




○	BEAM	LOR
1	32°	76%
2	44°	82%
3	51°	85%

ACCESSORY

BUDDY L Trimless Accessory**

A568-10-90

MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES

BUDDY L


BUDDY L Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D105 X D145mm

A478-00-06



COLOUR | W | N | WG | NG | WN | G | MATERIAL | AL | PC/PMMA

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



BUDDY L Trimless

		CCT	Beam	LOR
BUDDY L Trimless	A568-10- -0- W N G	2700K	32° / 44° / 51°	
	A568-10- -1- W N G	3000K	32° / 44° / 51°	
	A568-10- -3- W N G	3500K	32° / 44° / 51°	
	A568-10- -2- W N G	4000K	32° / 44° / 51°	
BUDDY L Trimless Super Spot	A568-10-00- W N G	2700K	13°	67%
	A568-10-01- W N G	3000K	13°	67%
	A568-10-03- W N G	3500K	13°	67%
	A568-10-02- W N G	4000K	13°	67%

IP54

|

CRI>90

|

L80B10
>66.000h

MacAdam Step 2

EXCL*

EXCL**

Ø105

UGR <19

		CCT	Beam	LOR
BUDDY L Trimless Tunable White	A568-11-17- W N G	1800-4000K	29°	78%
	A568-11-18- W N G	2700-5000K	29°	78%
	A568-11-27- W N G	1800-4000K	41°	83%
	A568-11-28- W N G	2700-5000K	41°	83%
	A568-11-37- W N G	1800-4000K	51°	84%
	A568-11-38- W N G	2700-5000K	51°	84%
BUDDY L Trimless DIM to warm	A568-12-39- W N G	1800-3000K	56°	82%

IP54

|

CRI>90

|

L80B10
>55.000h

MacAdam Step 3

EXCL*

EXCL**

Ø105

UGR <19


	BEAM	LOR
1	32°	76%
2	44°	82%
3	51°	85%

ACCESSORY

BUDDY L Trimless Accessory**

A568-10-90

MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES

BUDDY L


BUDDY L Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D105 X D145mm

A478-00-06



COLOUR | W | N | WG | NG | WN | G | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



BUDDY L Tilt

									CCT	Beam	LOR
BUDDY L Tilt	A569-00-	○ -0-	W N	WG	NG	WN			2700K	32° / 44° / 51°	○
	A569-00-	○ -1-	W N	WG	NG	WN			3000K	32° / 44° / 51°	○
	A569-00-	○ -3-	W N	WG	NG	WN			3500K	32° / 44° / 51°	○
	A569-00-	○ -2-	W N	WG	NG	WN			4000K	32° / 44° / 51°	○
BUDDY L Tilt Super Spot	A569-00-00-		W N	WG	NG	WN			2700K	13°	67%
	A569-00-01-		W N	WG	NG	WN			3000K	13°	67%
	A569-00-03-		W N	WG	NG	WN			3500K	13°	67%
	A569-00-02-		W N	WG	NG	WN			4000K	13°	67%

III

IP54

CRI>90

L80B10
> 66.000h

MacAdam
Step 2

EXCL*

355°

25°

Ø105



									CCT	Beam	LOR
BUDDY L Tilt Tunable White	A569-01-17-		W N	WG	NG	WN			1800-4000K	29°	78%
	A569-01-18-		W N	WG	NG	WN			2700-5000K	29°	78%
	A569-01-27-		W N	WG	NG	WN			1800-4000K	41°	83%
	A569-01-28-		W N	WG	NG	WN			2700-5000K	41°	83%
	A569-01-37-		W N	WG	NG	WN			1800-4000K	51°	84%
	A569-01-38-		W N	WG	NG	WN			2700-5000K	51°	84%
BUDDY L Tilt DIM to warm	A569-02-39-		W N	WG	NG	WN			1800-3000K	56°	82%

III

IP54

CRI>90

L80B10
> 55.000h

MacAdam
Step 3

EXCL*

355°

25°

Ø105



○	BEAM	LOR
1	32°	76%
2	44°	82%
3	51°	85%


ACCESSORY

BUDDY L Trimless Accessory**

A569-10-90


MANDATORY FOR INSTALLATION

20






Ø145



Ø112



97



MIN 120

↑↑↑ IP54



OPTIONAL ACCESSORIES

BUDDY L Tilt


BUDDY L Tilt Trimless

High Chromatic LED


NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D105 X D145mm

A478-00-06



Ø105



Ø145

COLOUR | W  | N  | WG  | NG  | WN  | G  | MATERIAL |  AL |  PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



BUDDY L Tilt Trimless

		CCT	Beam	LOR
BUDDY L Tilt Trimless	A569-10- 0 -0- W N G	2700K	32° / 44° / 51°	0
	A569-10- 0 -1- W N G	3000K	32° / 44° / 51°	0
	A569-10- 0 -3- W N G	3500K	32° / 44° / 51°	0
	A569-10- 0 -2- W N G	4000K	32° / 44° / 51°	0
BUDDY L Tilt Trimless Super Spot	A569-10-00- W N G	2700K	13°	67%
	A569-10-01- W N G	3000K	13°	67%
	A569-10-03- W N G	3500K	13°	67%
	A569-10-02- W N G	4000K	13°	67%

III

IP54

CRI>90

L80B10
> 66.000 h

MacAdam Step 2

EXCL*

EXCL**

25°

Ø105

		CCT	Beam	LOR
BUDDY L Tilt Trimless Tunable White	A569-11-17- W N G	1800-4000K	29°	78%
	A569-11-18- W N G	2700-5000K	29°	78%
	A569-11-27- W N G	1800-4000K	41°	83%
	A569-11-28- W N G	2700-5000K	41°	83%
	A569-11-37- W N G	1800-4000K	51°	84%
	A569-11-38- W N G	2700-5000K	51°	84%
BUDDY L Tilt Trimless DIM to warm	A569-12-39- W N G	1800-3000K	56°	82%

III

IP54

CRI>90

L80B10
> 55.000 h

MacAdam Step 3

EXCL*

EXCL**

25°

Ø105

0	BEAM	LOR
1	32°	76%
2	44°	82%
3	51°	85%

ACCESSORY

BUDDY L Trimless Accessory**

A569-10-90

MANDATORY FOR INSTALLATION

20

Ø145

Ø100

97

MIN 120

↑↑↑

IP54

OPTIONAL ACCESSORIES

BUDDY L Tilt

BUDDY L Tilt Trimless

High Chromatic LED

NOT SOLD SEPARATELY | AFFECTS THE LIGHTING PARAMETERS

TRIMLESS TOOL D105 X D145mm

A478-00-06

Ø105

Ø145

COLOUR | W | N | WG | NG | WN | G | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



BUDDY L Wall Washer

						CCT	LOR
BUDDY L Wall Washer	A573-00-10-	W	N	WN		2700K	54%
	A573-00-11-	W	N	WN		3000K	54%
	A573-00-13-	W	N	WN		3500K	54%
	A573-00-12-	W	N	WN		4000K	54%

III

IP20

CRI>90

L80B10
>66,000h

MacAdam
Step 2

EXCL*

360°

Ø105

						CCT	LOR
BUDDY L Wall Washer Tunable White	A573-01-17-	W	N	WN		1800-4000K	54%
	A573-01-18-	W	N	WN		2700-5000K	54%

III

IP20

CRI>90


L80B10
>55,000h

MacAdam
Step 3

EXCL*


360°

Ø105



COLOUR | W ☐ | N ☒ | WN ☐ | MATERIAL | AL ☒ | PC/PMMA ☐ |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS



BUDDY L Wall Washer Trimless

					CCT	LOR
BUDDY L Wall Washer Trimless	A573-10-10-	W	N		2700K	54%
	A573-10-11-	W	N		3000K	54%
	A573-10-13-	W	N		3500K	54%
	A573-10-12-	W	N		4000K	54%

III

IP20

CRI>90

L80B10
>66.000h

					CCT	LOR
BUDDY L Wall Washer Trimless Tunable White	A573-11-17-	W	N		1800-4000K	54%
	A573-11-18-	W	N		2700-5000K	54%

III

IP20

CRI>90

L80B10
>55.000h


ACCESSORY

BUDDY L Wall Washer

Trimless Accessory**

A573-10-90


MANDATORY FOR INSTALLATION



OPTIONAL ACCESSORIES

TRIMLESS TOOL D105 X D145mm






A478-00-06



COLOUR | W □ | N ■ | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

BUDDY L DRIVERS

*DRIVER OPTIONS				P	I	CCT	Flux			
BUDDY L 1 Buddy L Buddy L Trimless Buddy L Tilt Buddy L Tilt Trimless		 NO DIM	0433-01-37	8,1W	250mA	2700K	1500 lm			
						3000K	1560 lm			
						3500K	1600 lm			
						4000K	1600 lm			
BUDDY L 2 Buddy L Buddy L Trimless Buddy L Tilt Buddy L Tilt Trimless Buddy L Wall Washer Buddy L Wall Washer Trimless		 NO DIM	0433-00-21	11,5W	350mA					
		 DALI	0433-01-40			2700K	2010 lm			
						3000K	2090 lm			
		 CASAMBI	0433-01-43			3500K	2120 lm			
						4000K	2120 lm			
		 PHASE CUT	0433-01-39							
	BUDDY L Super Spot		 NO DIM			0433-01-38	11,6W	650mA	2700K	1430 lm
3000K				1510 lm						
		 DALI	0433-01-41	3500K	1570 lm					
				4000K	1610 lm					
		 CASAMBI	0434-01-98							
BUDDY L Tunable White		 DALI	0433-01-42	11,6W	350mA	1800-4000K	1270 lm			
						2700-5000K	1630 lm			
BUDDY L DIM to warm		 DALI	0433-01-40	11,6W	350mA	1800-3000K	1280 lm			
		 CASAMBI	0433-01-43							
	 PHASE CUT	0433-01-39								

220
240 V~ | 48V PLEASE CONSULT



BUDDY Surface

								CCT	Beam	LOR
BUDDY Surface	A594-00-	○ -0-	WT NT WTG NTG WTW					2700K	29° / 43° / 54°	○
	A594-00-	○ -1-	WT NT WTG NTG WTW					3000K	29° / 43° / 54°	○
	A594-00-	○ -3-	WT NT WTG NTG WTW					3500K	29° / 43° / 54°	○
	A594-00-	○ -2-	WT NT WTG NTG WTW					4000K	29° / 43° / 54°	○
BUDDY Surface Super Spot	A594-00-00-		WT NT WTG NTG WTW					2700K	12°	62%
	A594-00-01-		WT NT WTG NTG WTW					3000K	12°	62%
	A594-00-03-		WT NT WTG NTG WTW					3500K	12°	62%
	A594-00-02-		WT NT WTG NTG WTW					4000K	12°	62%

III

IP20

CRI>90

L80B10
>66.000 h

L80B10
>55.000 h (Super Spot)

MacAdam
Step 2

OPTIONS*

EXCL*

UGR <19

								CCT	Beam	LOR
BUDDY Surface Tunable White	A594-01-17-	WT NT WTG NTG WTW						1800-4000K	28°	85%
	A594-01-18-	WT NT WTG NTG WTW						2700-5000K	28°	85%
	A594-01-27-	WT NT WTG NTG WTW						1800-4000K	43°	86%
	A594-01-28-	WT NT WTG NTG WTW						2700-5000K	43°	86%
	A594-01-37-	WT NT WTG NTG WTW						1800-4000K	55°	81%
	A594-01-38-	WT NT WTG NTG WTW						2700-5000K	55°	81%
BUDDY Surface DIM to warm	A594-02-39-	WT NT WTG NTG WTW						1800-3000K	54°	75%

III

IP20

CRI>90

L80B10
>55.000 h


MacAdam
Step 3

OPTIONS*

EXCL*

UGR <19














○	BEAM	LOR	OPTIONAL ACCESSORY			FINISHING	Body	Lampshade
1	29°	82%	BUDDY Surface			WT	WT ☐	N ☒
2	43°	83%	High Chromatic LED			NT	NT ☒	N ☒
3	54°	80%	NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS			WTG	WT ☐	G ☒
						NTG	NT ☒	G ☒
						WTW	WT ☐	W ☐



COLOUR | WT ☐ | NT ☒ | WTG ☐ | NTG ☒ | WTW ☐ | MATERIAL | AL | PC/PMMA |

COLOURS MAY AFFECT THE LIGHTING PARAMETERS

BUDDY Surface DRIVERS

*DRIVER OPTIONS				P	I	CCT	Flux
BUDDY Surface 1		 NO DIM	0434-01-85	4W	125mA	2700K	770 lm
						3000K	800 lm
						3500K	810 lm
						4000K	820 lm
BUDDY Surface 2		 NO DIM	0434-01-86	6,6W	200mA	2700K	1190 lm
						3000K	1240 lm
						3500K	1250 lm
						4000K	1260 lm
BUDDY Surface 2		 NO DIM	0433-01-37	6,6W	200mA		
		 DALI	0434-01-29			2700K	1440 lm
		 CASAMBI	0434-03-02			3000K	1500 lm
		 PHASE CUT	0434-03-03			3500K	1520 lm
						4000K	1530 lm
BUDDY Surface Super Spot		 NO DIM	0433-00-27	8,8W	700mA	2700K	970 lm
						3000K	1020 lm
		 DALI	0434-03-01			3500K	1060 lm
BUDDY Surface Tunable White		 DALI	0434-01-96	8,5W	500mA	1800-4000K	860 lm
						2700-5000K	1030 lm
BUDDY Surface DIM to warm		 DALI	0434-01-94	6W	350mA	1800-3000K	670 lm
		 PHASE CUT	0434-01-95				

220
240 V~ | DRIVER MUST BE PLACED ON REMOTE

BUDDY
PURPOSEFUL
DESIGN

by **ARKOSLIGHT**