



Ref. Certif. No.

ES2782-AENOR

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

RECESSED LUMINAIRE

Name and address of the applicant

ARKOSLIGHT, S.L.
PI EL OLIVERAL, CL. N
46394 RIBARROJA DEL TURIA (Valencia - Spain)

Name and address of the manufacturer

SAME AS ABOVE

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

SEE ANNEX

Trademark (if any)

ARKOSLIGHT

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

SEE ANNEX

Additional information (if necessary may also be reported on page 2)

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020
IEC 60598-2-2:2023

As shown in the Test Report Ref. No. which forms part of this Certificate

2025050395B1

This CB Test Certificate is issued by the National Certification Body

AENOR CONFÍA S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2025-06-30

Signature: Rafael GARCÍA MEIRO
CEO

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

RECESSED LUMINAIRE

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
DUOMO 1 IP65 / IP 20 A285-01	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 16,5 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
DUOMO 1 IP65 / IP 65 A285-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 16,5 W max.	LED (COB)	IP 65 / IP 65	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
DUOMO 2 IP65 / IP 20 A285-02	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 41 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
DUOMO 2 IP65 / IP 65 A285-12	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 41 W max.	LED (COB)	IP 65 / IP 65	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
HIDDEN 1 A200-1	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
HIDDEN 2 A200-2	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
HUBBLE DOUBLE 1 A277-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 16,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
HUBBLE DOUBLE 2 A277-21	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 30,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
HUBBLE DOUBLE 3 A277	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 41 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
HUBBLE 1 A276-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 16,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
HUBBLE 2 A276-21	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 30,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K
HUBBLE 3 A276	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 41 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC BLUE 1 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC BLUE 2 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC BLUE 3 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC 1 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC 2 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX ASYMMETRIC 3 A071	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
LEX BLUE 1 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX BLUE 2 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX BLUE 3 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 1 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 2 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 205 1 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 205 2 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 205 3 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
LEX 3 A070	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
NANO RECESSED A539-0	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
NANO TILT A541-0	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
NANO TRIMLESS A540-0	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL A010-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL A010-12	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL A010-13	ARKOSLIGHT	220-240 V~ 50/60 Hz	3 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL A010-14	ARKOSLIGHT	220-240 V~ 50/60 Hz	4 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL mini 1 A196-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 7,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL mini 2 A196-21	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 7,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
ORBITAL mini 3 A196-31	ARKOSLIGHT	220-240 V~ 50/60 Hz	3 x 7,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL TRIMLESS A010-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL TRIMLESS A010-12	ARKOSLIGHT	220-240 V~ 50/60 Hz	2 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL TRIMLESS A010-13	ARKOSLIGHT	220-240 V~ 50/60 Hz	3 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
ORBITAL TRIMLESS A010-14	ARKOSLIGHT	220-240 V~ 50/60 Hz	4 x 12 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
POINTER 11 W A271	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 11 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
POINTER 5 W A271	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
POINTER 7 W A271	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 7 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT BIG 1 A448-1	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 11,8 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
SHOT LIGHT BIG 1 A449-1	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 11,8 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT BIG 2 A448-2	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT BIG 2 A449-2	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17,5 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT BIG 3 A448-3	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 25,3 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT BIG 3 A449-3	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 25,3 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 1 ASYMETRIC A297-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 1 A297-01	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 1 A297-21	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 2 ASYMETRIC A297-12	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 6,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
SHOT LIGHT M 2 A297-02	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 6,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 2 A297-22	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 6,5 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 3 ASYMETRIC A297-13	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 3 A297-03	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M 3 A297-23	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10,3 W max.	LED (COB)	IP 65 / IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M1 ASYMETRIC TRIMLESS A298-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M1 TRIMLESS A298-01	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M2 ASYMETRIC TRIMLESS A298-12	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 7 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M2 TRIMLESS A298-02	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 7 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable

ANNEX TO CB CERTIFICATE N° ES2782-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Type reference	Trade mark	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Mains connections	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
SHOT LIGHT M3 ASYMMETRIC TRIMLESS A298-13	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SHOT LIGHT M3 TRIMLESS A298-03	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 10,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX L Recessed 1 A287-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 11,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX L Recessed 2 A287-2	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 24,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX M Recessed 1 A332-11	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 11,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX M Recessed 2 A332-2	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 17 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX S Recessed A334-0	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 8,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable
SIX XS Recessed A336-0	ARKOSLIGHT	220-240 V~ 50/60 Hz	1 x 4,5 W max.	LED (COB)	IP 20	Bornes terminals	Apta para superficies normalmente inflamables suitable for normally flammable surfaces	Clase class II	Montaje horizontal horizontal fixing	Max. 4000 K; no regulable y regulable non-dimmable and dimmable