




DIMENSIONS



AWARDS




Name	SALT 3 2700K WW
Reference	A2200310WW
Color	White-White
Power of the system	9016 & 9016
Category	SUSPENSION
PRODUCT	
LIGHTING INFORMATION	
Light source	LED
Gross luminous flux	2800 Lm
Power	22 W
Power values of the system	25,88 W
Colour temperature	2700 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 2
Light beam angle	77°
Lighting efficiency	79%
Efficacy	127 Lm/W
Current intensity	700 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	⊕
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=80°C) >60.000h
OTHER DATA	
Ingress Protection	IP20
Cord length	2 m
Fast adjustment tensioner	Yes
Weight	4600 g.
Packaged weight	5329,4 g.
Packaging dimensions	452 × 452 × 418 mm.
Units per package	1
Materials	Aluminium / Polymethyl Methacrylate




High Bay light fitting performance combined with the design of a unique decorative piece. Salt integrates driver and heat dissipation into the design of the fitting itself and achieves on the one hand an excellent thermal management and on the other hand the freedom to hang the fixture at any desired height. And to prevent glare, Salt disposes of a diffuser covering the light source.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR												
ρ Ceiling	70	70	50	50	30	70	70	50	50	30		
ρ Walls	50	30	50	30	30	50	30	50	30	30		
ρ Floor	20	20	20	20	20	20	20	20	20	20		
Room Size	X	Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H		14.1	15.1	14.4	15.4	15.6	14.1	15.1	14.4	15.4	15.6
	3H		15.9	16.8	16.2	17.1	17.3	15.9	16.8	16.2	17.1	17.3
	4H		16.6	17.5	16.9	17.7	18.0	16.6	17.5	16.9	17.7	18.0
	6H		17.1	17.9	17.4	18.2	18.5	17.1	17.9	17.4	18.2	18.5
	8H		17.3	18.1	17.6	18.4	18.7	17.3	18.1	17.6	18.4	18.7
4H	12H		17.4	18.2	17.8	18.5	18.8	17.4	18.2	17.8	18.5	18.8
	2H		14.7	15.6	15.0	15.9	16.1	14.7	15.6	15.0	15.9	16.1
	3H		16.7	17.5	17.1	17.8	18.1	16.7	17.5	17.1	17.8	18.1
	4H		17.5	18.2	17.9	18.5	18.9	17.5	18.2	17.9	18.5	18.9
	6H		18.2	18.8	18.6	19.1	19.5	18.2	18.8	18.6	19.1	19.5
8H	8H		18.4	19.0	18.9	19.3	19.8	18.4	19.0	18.9	19.3	19.8
	12H		18.6	19.1	19.0	19.5	19.9	18.6	19.1	19.0	19.5	19.9
	4H		17.8	18.4	18.3	18.8	19.2	17.8	18.4	18.3	18.8	19.2
	6H		18.6	19.1	19.1	19.5	19.9	18.6	19.1	19.1	19.5	19.9
	8H		19.0	19.3	19.4	19.8	20.3	19.0	19.3	19.4	19.8	20.3
12H	12H		19.2	19.5	19.7	20.0	20.5	19.2	19.5	19.7	20.0	20.5
	4H		17.9	18.3	18.3	18.7	19.2	17.9	18.3	18.3	18.7	19.2
	6H		18.7	19.1	19.2	19.5	20.0	18.7	19.1	19.2	19.5	20.0
8H		19.1	19.4	19.6	19.9	20.4	19.1	19.4	19.6	19.9	20.4	
Variation of the observer position for the luminaire distances S												
S = 1.0H	+0.3 / -0.3					+0.3 / -0.3						
S = 1.5H	+0.7 / -0.5					+0.7 / -0.5						
S = 2.0H	+1.3 / -0.8					+1.3 / -0.8						
Standard table	BK05					BK05						
Correction Summand	-2.8					-2.8						
Corrected Glare Indices referring to 2800lm Total Luminous Flux												