




DIMENSIONS



ACCESSORIES



SWAP ADD-ON BEZEL
EXCLUDED. NOT COMPATIBLE.

AWARDS



Name	SWAP IP54 SQUARE ASYM 6W DALI DIM TO WARM W
Reference	A2553339W54
Color	Matt white
Category	CEILING RECESSED

PRODUCT

Light source	LED
Gross luminous flux	640 Lm
Power	6 W
Power values of the system	6,82 W
Colour temperature	Dim to warm 1800 - 3000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 3
Light beam angle	52°
Unified Glare Rating	UGR<19
Lighting efficiency	76%
Efficacy	107 Lm/W
Current intensity	350 mA
Dimming	DALI / Push - Other DIM, please consult
Driver	Incl. - Fast Connect
Fast connection of the driver to the mains supply	Please Consult
Emergency power supply	Please Consult
Electrical insulation class	□
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B20 (Tj=85°C) >55.000h


OTHER DATA

Ingress Protection	IP54
Recess measurements	85 × 85 mm.
Weight	0,25 g.
Packaged weight	0,2985 g.
Units per package	1
Materials	Aluminium / Polycarbonate



Swap is a ceiling recessed LED spotlight whose main features are its minimalist aspect, its perfect integration into the ceiling, and considerable visual comfort, thanks to the small reflector that is set back with respect to the ceiling plane. When it is switched on, its matte finish shade generates an attractive effect, a discrete circle of light. It includes an add-on bezel that can be used optionally to cover larger recess diameters.

POLAR DIAGRAM



CONICAL DIAGRAM

