




## DIMENSIONS





## ACCESSORIES







	PRODUCT
Name	SHOT LIGHT M ASYMM TRIMLESS 1 3000K W
Reference	A2981111W
Color	White
RAL	Colour in the mass looks alike RAL 9016
Category	CEILING RECESSED
	LIGHTING INFORMATION
Light source	LED
Gross luminous flux	700 Lm
Power	5 W
Power values of the system	6,66 W
Colour temperature	3000 K
Colour Rendering Index	CRI>90
Chromatic stability	MacAdam Step 2
Light beam angle	38°
Lighting efficiency	83%
Efficacy	140 Lm/W
Current intensity	150 mA
Dimming	No Dim - Other DIM, please consult
Control through bluetooth	Please Consult
Driver	Included - Connected
Emergency power supply	Please Consult
Electrical insulation class	
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A++
LED lifespan	L80B10 (Tc=85°C) >60.000h
	OTHER DATA
Ingress Protection	IP20
Recess measurements	Ø85 mm.
Weight	165 g.
Packaged weight	220 g.
Packaging dimensions	101 × 95 × 88 mm
Units per package	1
Materials	Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate




A luminary conceived to be a discreet point of light in the ceiling that hides the illumination source from sight and aims to offer maximum visual comfort. In order to achieve this, it has an anti-glare screen and a specifically designed micro-reflector that generates a perfectly defined light beam.






## POLAR DIAGRAM



## CONICAL DIAGRAM





FOR COMMERCIAL PRODUCT SHOWCASING

Vivid Model Colour Temperature	2700K	3000K	3500K	4000K	Light Pink
Reading			•	•	
Fruits & Vegetables		•	•		
⊕ Bakery	•				
2 Retail		•	•		
Cosmetics			•	•	
Q; Meat					•
Fish				•	
Seafood				•	•




For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes. It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object.

This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a «special saturation parameter», capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate diode and specific phosphor coating are carefully selected.



MANDATORY ACCESSORIES



	PRODUCT
Model	Shot Light M A
Reference	A2981000
Material	Iron
Coating	Zinc plated
Category	Accessories

11(05001	
Shot Light M Asymmetric Trimless accessory	
A2981000	
Iron	
Zinc plated	
Accessories	

