




DIMENSIONS



AWARDS




Name	BLACK FOSTER SUSP 1600 4000K NT
Reference	A3212012NT
Color	Textured black
Power of the system	9005
Category	SUSPENSION
PRODUCT	
Light source	LED
Gross luminous flux	3750 Lm
Power	31,5 W
Power values of the system	37,50 W
Colour temperature	4000 K
Colour Rendering Index	CRI>90
Chromatic stability	Mac Adam Step 3
Light beam angle	38°
Unified Glare Rating	UGR<19
Lighting efficiency	90%
Efficacy	119 Lm/W
Current intensity	700 mA
Control through bluetooth	Please Consult
Driver	Included
Electrical insulation class	<input type="checkbox"/>
Voltage	220 V/240 V
Frequency	50/60 Hz
Energy efficiency	A+
LED lifespan	L80B10 (Tc=85°C) >60.000h
LIGHTING INFORMATION	
Ingress Protection	IP20
Cord length	2 m
Fast adjustment tensioner	Yes
Weight	4370 g.
Packaged weight	5790 g.
Packaging dimensions	D145 × 1735 mm.
Units per package	1
Materials	Aluminium / Acrylonitrile Butadiene Styrene / Polycarbonate
OTHER DATA	




Black Foster Suspension es la luminaria que traslada el aclamado efecto 'The Invisible Black' a un sistema lineal de suspensión. Se compone de una serie de módulos de emisión de luz dentro de un foseado metálico. Ofrece iluminación "no-glare" en aplicaciones sobre mesas y conserva la misma estética tanto encendida como apagada.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis					
2H	2H	-15.1	-14.4	-14.8	-14.2	-14.0	-15.3	-14.7	-15.1	-14.5	-14.3
	3H	-10.9	-10.4	-10.7	-10.1	-9.9	-13.4	-12.9	-13.2	-12.6	-12.4
	4H	-10.9	-10.4	-10.6	-10.1	-9.9	-8.9	-8.4	-8.6	-8.1	-7.9
	6H	-9.6	-9.1	-9.3	-8.8	-8.5	-5.9	-5.4	-5.6	-5.1	-4.8
4H	8H	-8.4	-7.9	-8.1	-7.7	-7.4	-5.4	-4.9	-5.0	-4.6	-4.3
	12H	-7.8	-7.4	-7.5	-7.1	-6.8	-5.1	-4.7	-4.8	-4.4	-4.0
	2H	-12.9	-12.4	-12.6	-12.1	-11.9	-13.1	-12.5	-12.8	-12.3	-12.0
8H	3H	-9.8	-9.4	-9.5	-9.1	-8.7	-11.2	-10.7	-10.8	-10.4	-10.1
	4H	-9.4	-9.0	-9.0	-8.7	-8.4	-7.1	-6.7	-6.7	-6.4	-6.0
	6H	-8.0	-7.6	-7.6	-7.3	-6.9	-3.5	-3.2	-3.1	-2.9	-2.5
	8H	-6.3	-6.0	-5.9	-5.6	-5.2	-3.0	-2.7	-2.5	-2.3	-1.9
12H	12H	-5.8	-5.6	-5.4	-5.2	-4.8	-2.6	-2.4	-2.2	-2.0	-1.6
	4H	-7.2	-6.9	-6.8	-6.6	-6.2	-6.0	-5.7	-5.6	-5.3	-4.9
	6H	-5.6	-5.4	-5.2	-5.0	-4.5	-2.2	-2.0	-1.7	-1.6	-1.1
	8H	-3.9	-3.7	-3.4	-3.3	-2.8	-1.6	-1.4	-1.1	-1.0	-0.5
12H	12H	-3.5	-3.4	-3.0	-2.9	-2.4	-0.9	-0.8	-0.5	-0.3	0.2
	4H	-6.7	-6.4	-6.2	-6.0	-5.6	-5.9	-5.6	-5.5	-5.2	-4.8
	6H	-4.9	-4.7	-4.4	-4.3	-3.8	-2.0	-1.9	-1.6	-1.4	-1.0
8H	-3.3	-3.2	-2.8	-2.7	-2.2	-1.4	-1.2	-0.9	-0.8	-0.3	
Variation of the observer position for the luminaire distances S											
S = 1.0H	+4.3 / -1.8					+2.3 / -0.6					
S = 1.5H	+6.8 / -2.0					+4.2 / -1.0					
S = 2.0H	+8.8 / -2.6					+5.9 / -2.3					
Standard table	---					---					
Correction	---					---					
Summand	---					---					
Corrected Glare Indices referring to 3750lm Total Luminous Flux											