




DIMENSIONS



ACCESSORIES



HIGH CHROMATIC LED



TRACK 48V OPTIONS

AWARDS



PRODUCT

| | |
|---------------------|------------------------|
| Name | SIX M 48V 38° 3000K WT |
| Reference | A3300131WT |
| Color | Textured white |
| Power of the system | 9016 |
| Category | TRACKLIGHTS |

LIGHTING INFORMATION

| | |
|-----------------------------|---------------------------|
| Light source | LED |
| Gross luminous flux | 2130 Lm |
| Power | 17 W |
| Power values of the system | 18,28 W |
| Colour temperature | 3000 K |
| Colour Rendering Index | CRI>90 |
| Chromatic stability | Mac Adam Step 2 |
| Light beam angle | 38° |
| Lighting efficiency | 93% |
| Efficacy | 125 Lm/W |
| Current intensity | 500 mA |
| Control through bluetooth | Please Consult |
| Driver | Included |
| Electrical insulation class | III |
| Voltage | 48 V |
| Frequency | 0 Hz |
| Energy efficiency | A+ |
| LED lifespan | L80B10 (Tj=85°C) >60.000h |


OTHER DATA

| | |
|----------------------|---------------------------|
| Ingress Protection | IP20 |
| Swivel angle | 310° |
| Rotation angle | 360° |
| Track type | Track 48V |
| Weight | 303 g. |
| Packaged weight | 375 g. |
| Packaging dimensions | 188 x 165 x 53 mm. |
| Units per package | 1 |
| Materials | Aluminium / Polycarbonate |




Six 48V is a family of spotlights for low voltage tracklight applications that stands out for its lightness and elegance. Available in L, M, S, XS and XS Double, its body; disk looking, rounded shaped, encloses an innovative combination of reflector and lens. The combined action of both, allows Six to direct light rays with the maximum uniformity in a very small distance that, at the same time, has made possible its differential design-reduced and minimalist-. In addition, Six can be freely articulated due to its airy arm which allows the spotlight to be orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM



HIGH CHROMATIC LED

ARKOSLIGHT®

FOR COMMERCIAL PRODUCT SHOWCASING

| Vivid Model Colour Temperature | 2700K | 3000K | 3500K | 4000K | Light Pink |
|-----------------------------------|-------|-------|-------|-------|------------|
| 📖 Reading | | | • | • | |
| 🥬 Fruits & Vegetables | | • | • | | |
| 🍰 Bakery | • | | | | |
| 👤 Retail | | • | • | | |
| 💄 Cosmetics | | | • | • | |
| 🥩 Meat | | | | | • |
| 🐟 Fish | | | | • | |
| 🐠 Seafood | | | | • | • |



For some of its products, Arkoslight offers the possibility to provide them with a special LED, designed to create an illumination focused on visually promoting goods or products for commercial purposes. It is a high chromaticity LED, capable of identifying the colour shades that produce a positive psychological perception of the illuminated object.


This special LED lighting source offers a much more attractive and intense colour range than a conventional LED, besides being much wider. Technically, this is possible thanks to a special LED setting that includes a «special saturation parameter», capable of highlighting the objects colours and materials in such a way that they seem more attractive within the visible light spectrum. To achieve this performance, in each case, the appropriate diode and specific phosphor coating are carefully selected.

TRACK 48V TRIMLESS


ARKOSLIGHT®



TRACK 48V SURFACE

Available on request. Please consult.



| | |
|---------------------------------|-----------------|
| TRACK 48V 1M | A338-01-00- N |
| TRACK 48V 2M | A338-02-00- N |
| TRACK 48V 3M | A338-03-00- N |
| TRACK 48V Corner 90° One Plane | A338-04-00- N |
| TRACK 48V Corner 90° Two Planes | A338-05-00- N |



| | | | P | I | D |
|--------------------------------------|---|------------|------|-----|------------------|
| CONSTANT VOLTAGE LED POWER SUPPLY |  NO DIM | 0434-01-21 | 75W | 48V | 180 x 52 x 30mm |
| | | 0434-01-22 | 150W | 48V | 240 x 60 x 49mm |
| |  DALI | 0434-01-19 | 75W | 48V | 235 x 100 x 31mm |
| | | 0434-01-20 | 150W | 48V | 235 x 100 x 31mm |

CABLE SECTION AND LENGHT BETWEEN TRACK 48V AND POWER SUPPLY

| TRACK LENGHT (m) | | 10 | | | 20 | | 29 |
|------------------|---------------------|----|----|----|----|----|----|
| CABLE LENGHT (m) | | 1 | 10 | 20 | 1 | 10 | 1 |
| POWER (W) | CABLE SECTION (mm²) | | | | | | |
| 75W | 0,75mm² | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| | 1,5mm² | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 150W | 0,75mm² | ✓ | X | X | ✓ | X | ✓ |
| | 1,5mm² | ✓ | ✓ | X | ✓ | ✓ | ✓ |

COLOUR | N ■ RAL 9005 |

Recommended for installations where the profile can be installed before the false plasteboard ceiling (thickness 12,5mm.)

Calle N · Pol. Ind. EL OLIVERAL
46394 Ribarroja del Turia · Valencia (Spain)
Tel. +34 961 667 207 · Fax +34 961 667 054
info@arkoslight.com · www.arkoslight.com




TRACK 48V TRIMLESS

ARKOSLIGHT®

TRACK 48V SURFACE


Available on request. Please consult.

TRACK 48V 90° CORNER One Plane




*Electrical connection included

TRACK 48V 90° CORNER Two Planes




*Electrical connection included



TRACK 48V Live-End Connector

A338-00-01- | N |




TRACK 48V Central Connector

A338-00-02- | N |




TRACK 48V Short T-Bracket

A338-00-03



TRACK 48V Long T-Bracket

A338-00-04



TRACK 48V Straight Joiners (2 Units)

A338-00-05



TRACK 48V End

A338-00-06- | N |

TRACK 48V End Feed

A338-00-07- | N |

TRACK 48V Suspension Kit

A338-00-08

See accessories quantities*

TRACK 48V Clamp for M6 ROD

A338-00-09

See accessories quantities*

TRACK 48V Track Clamp

A338-00-10

See accessories quantities*

* SUGGESTED MOUNTING ACCESSORIES QUANTITIES

1000 mm - 2 Pcs.

2000 mm - 3 Pcs.

3000 mm - 4 Pcs.

COLOUR | N ■ RAL 9005 |

Recommended for installations where the profile can be installed before the false plasteboard ceiling (thickness 12,5mm.)

Calle N · Pol. Ind. EL OLIVERAL

46394 Ribarroja del Turia · Valencia (Spain)

Tel. +34 961 667 207 · Fax +34 961 667 054

info@arkoslight.com · www.arkoslight.com

