

## Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 920-337-2175 • Fax: 920-337-9410

PRODUCT: MiraClean<sup>TM</sup> Stock # 0201

**Description:** Mild alkaline liquid cleaner with butyl solvent. Used for spot cleaning grease

oil, tar, and other stubborn soils. May also be used as a presoak detergent that

rinses easily and has a low cost per car.

Color: Green

**Scent:** Butyl Solvent

Foaming Ability: Low to Moderate

Features = Benefits

Titratable = Quickly determine dilution ratio.

Biodegradable = Acceptable to waste water treatment.

Multiple uses = One Product saves time and space.

<b>Application</b>		<b>Dilution Ratios</b>	
	<b>Strongest</b>	Weakest	<b>Average</b>
General Spot Cleaning:	1:5	1:20	1:10
Tar and other tough soils:	1:3	1:6	1:4
Engine Cleaner/degreaser:	1:5	1:20	1:10
Presoak detergent:	1:30	1:70	1:40

Required strength of product dilution will vary depending on cleaning conditions and type and condition of equipment used.

### **Guidelines for Application**

MiraClean<sup>TM</sup> has multiple uses. The following guidelines are applicable to most uses.

<u>Water</u> Use soft water whenever possible.

**Quality**:

**Solution** Cold to warm water (100°F).

**Temperatures:** 

**<u>Dwell time</u>**: Generally increased dwell time will increase cleaning performance in all

types of systems up to about 30 seconds. After that there is little advantage

to longer contact time.



# Product Application & Results

1997 American Blvd. • P.O. Box 5606 • De Pere, WI 54115-5606 • 920-337-2175 • Fax: 920-337-9410

**PRODUCT:** 

### MiraClean TM

Stock # 0201

#### **Alternative Products**

**Resolve**<sup> $\mathsf{TM}$ </sup> is a more effective option for tar and asphalt removal.

Titration Chart For MiraClean <sup>TM</sup>			
	Dilution	Drops	
This chart uses standard	1:10	64	
"Alkaline Titrant" and a water	1:15	43	
blank must be titrated to	1:20	32	
	1:30	22 16	
subtract from your total drops	1:40	10	
before comparing to the curve.	1:80	9	
	1:100	7	

0201-0815 p2

