

SUBMITTAL SHEET

JOB NAME	ITEM TAG
JOB LOCATION	PART NUMBER
CONTRACTOR	DATE
ENGINEER APPROVAL	DATE



NO LEAD FORGED STEEL DIELECTRIC UNION (1/2" TO 2")

T-571NL (1/2" - 2")

Designed to reduce galvanic corrosion where two dissimilar metals are joined. Self-aligning, non-conductive elastomer gasket and thermoplastic insert create a positive seal and complete isolation between the tubing and piping ends.

High-strength, galvanized forged steel construction make them ideal for residential and commercial applications.

**Note: Sizes 2-1/2" to 4" are flange-type body construction.
See T-571NL 2-1/2" to 4" submittal sheet for details.*

Working Pressure, Non Shock (PSI)

Cold working pressure (CWP): 200 psi up to 180° F

275° F or 30 psi WSP (continuous) / 300° F (intermittent)*

**When equipped with the optional Gasket and Insert for Steam (not included, available separately).*




Pictured:
T-571NL (1/2" - 2")

MATERIAL SPECIFICATION

PART	MATERIAL	SPECIFICATION
1 Body	Forged carbon steel, galvanized	AISI 1008A
2 Union nut	Forged carbon steel, galvanized	AISI 1008A
3 Solder adapter	Lead-free forged brass	JIS C6806
4 Gasket	EPDM rubber	Commercial grade
5 Insert insulator	Nyloy	MG-0133N

DIMENSIONS

Size	A	B
1/2" FNPT x Swt	1.84	1.44
3/4" FNPT x Swt	2.07	1.63
3/4" FNPT x 1/2" Swt	1.86	1.63
1" FNPT x Swt	2.27	1.88
1" FNPT x 3/4" Swt	2.25	2.13
1-1/4" FNPT x Swt	2.48	2.26
1-1/2" FNPT x Swt	2.53	2.62
2" FNPT x Swt	2.70	3.51
1/2" MNPT x Swt	2.75	1.44
3/4" MNPT x Swt	2.98	1.63
3/4" MNPT x 1/2" Swt	2.75	1.63



Pictured
T-571NL (FNPT x Sweat)
Cut-away

Certifications/Listings:

Third-party certified.

NSF/ANSI 372: Drinking water system components - Lead content.

Standards:

ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch

ANSI/ASME B16.22: Wrot copper and copper alloy solder-joint pressure fittings