

IES ROAD REPORT



Light measurement results

Print date 12/11/2025

PHOTOMETRIC FILENAME : DE-C22-2700K-FL

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a
[TESTLAB] Viso - serial: n/a sensor serial: n/a - Test lab
[MANUFAC] B-K Lighting Inc
[ISSUEDATE] 12/11/2025
[LUMINAIRE] DE-C22-2700K-FL
[LUMCAT] N/A
[_SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DE-C22-2700K-FL
Item No.	
Manufacturer	B-K Lighting Inc

Main Light Measurement Results

Luminaire lumens	783 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	37.69 lm/W
Total Luminaire Watts	20.78 W
Upward Waste Light Ratio	0.0008%
Maximum Candela	1520 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0.1075 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0.1074 cd
Maximum Candela from 80 to <90 Degrees Vertical	5.48 cd
Correlated Color Temperature, CCT	2700 K
Color Rendering Index, CRI	90.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

IES ROAD REPORT



Light measurement results

Print date 12/11/2025

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	334.2	lm	42.68%
Medium (30-60°)	47.07	lm	6.011%
High (60-80°)	8.399	lm	1.073%
Very High (80-90°)	1.872	lm	0.2391%

Back Light

Low (0-30°)	334.2	lm	42.68%
Medium (30-60°)	47.07	lm	6.011%
High (60-80°)	8.399	lm	1.073%
Very High (80-90°)	1.872	lm	0.2391%

Uplight

Low (90-100°)	5.892	lm	0.7525%
High (100-180°)	0	lm	0%

Total

Sum	783	lm	100%
------------	------------	-----------	-------------

BUG RATING B1 U0 G0

