

IES ROAD REPORT



Light measurement results

Print date 12/16/2025

PHOTOMETRIC FILENAME : DE-LED-C22-FL-9-3K

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a
[TESTLAB] Viso - serial: n/a sensor serial: n/a - Test lab
[MANUFAC] B-K Lighting Inc
[ISSUEDATE] 12/16/2025
[LUMINAIRE] DE-LED-C22-FL-9-3K
[LUMCAT] N/A
[SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DE-LED-C22-FL-9-3K
Item No.	
Manufacturer	B-K Lighting Inc

Main Light Measurement Results

Luminaire lumens	738 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	35.52 lm/W
Total Luminaire Watts	20.78 W
Upward Waste Light Ratio	0.0008%
Maximum Candela	1433 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0.1013 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0.1013 cd
Maximum Candela from 80 to <90 Degrees Vertical	5.165 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index, CRI	90.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

IES ROAD REPORT

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	315	lm	42.68%
Medium (30-60°)	44.36	lm	6.011%
High (60-80°)	7.916	lm	1.073%
Very High (80-90°)	1.765	lm	0.2391%

Back Light

Low (0-30°)	315	lm	42.68%
Medium (30-60°)	44.36	lm	6.011%
High (60-80°)	7.916	lm	1.073%
Very High (80-90°)	1.765	lm	0.2391%

Uplight

Low (90-100°)	5.553	lm	0.7525%
High (100-180°)	0	lm	0%

Total			
Sum	738	lm	100%

BUG RATING B1 U0 G0

