

IES ROAD REPORT



Light measurement results

Print date 12/18/2025

PHOTOMETRIC FILENAME : DE-LED-TR-X123-FL-9-C

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] Viso LabSpion - serial: n/a sensor serial: n/a

[TESTLAB] Viso - serial: n/a sensor serial: n/a - Test lab

[MANUFAC] B-K Lighting INC

[ISSUEDATE] 12/18/2025

[LUMINAIRE] DE-LED-TR-X123-FL-9-C

[LUMCAT] N/A

[_SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DE-LED-TR-X123-FL-9-C
Item No.	
Manufacturer	B-K Lighting INC

Main Light Measurement Results

Luminaire lumens	1508 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	69.37 lm/W
Total Luminaire Watts	21.74 W
Upward Waste Light Ratio	0%
Maximum Candela	2714 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	2.415 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B2 U0 G0

IES ROAD REPORT



Light measurement results

Print date 12/18/2025

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	643.4	lm	42.67%
Medium (30-60°)	105.7	lm	7.007%
High (60-80°)	4.043	lm	0.2681%
Very High (80-90°)	0.8706	lm	57.73%

Back Light

Low (0-30°)	643.4	lm	42.67%
Medium (30-60°)	105.7	lm	7.007%
High (60-80°)	4.043	lm	0.2681%
Very High (80-90°)	0.8706	lm	57.73%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	1508	lm	100%
------------	-------------	-----------	-------------

BUG RATING B2 U0 G0

