

IES ROAD REPORT



Light measurement results

Print date 12/23/2025

PHOTOMETRIC FILENAME : DE-LED-TR-X99-FL

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a
[TESTLAB] UL Verification Services Inc.
[MANUFAC] B-K Lighting Inc
[ISSUE DATE] 12/23/2025
[LUMINAIRE] DE-LED-TR-X99-FL
[LUMCAT] N/A
[SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DE-LED-TR-X99-FL
Item No.	
Manufacturer	B-K Lighting Inc

Main Light Measurement Results

Luminaire lumens	1091 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	85.62 lm/W
Total Luminaire Watts	12.74 W
Upward Waste Light Ratio	0.0005%
Maximum Candela	1866 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	96.69 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	96.63 cd
Maximum Candela from 80 to <90 Degrees Vertical	1.547 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

IES ROAD REPORT



Light measurement results

Print date 12/23/2025

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	456	lm	41.8%
Medium (30-60°)	86.4	lm	7.92%
High (60-80°)	2.90	lm	0.266%
Very High (80-90°)	0.540	lm	0.0495%

Back Light

Low (0-30°)	456	lm	41.8%
Medium (30-60°)	86.4	lm	7.92%
High (60-80°)	2.90	lm	0.266%
Very High (80-90°)	0.540	lm	0.0495%

Uplight

Low (90-100°)	0.00530	lm	0.000486%
High (100-180°)	0	lm	0%

Total

Sum	1091	lm	100%
------------	------	----	------

BUG RATING B1 U0 G0

