

IES ROAD REPORT



Light measurement results

Print date 12/19/2025

PHOTOMETRIC FILENAME : DE-LED-X65-MFL

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002

[TEST] Viso LabSpion - serial: n/a sensor serial: n/a

[TESTLAB] Viso - serial: n/a sensor serial: n/a - Test lab

[MANUFAC] B-K LIGHTING INC

[ISSUEDATE] 12/19/2025

[LUMINAIRE] DE-LED-X65-MFL

[LUMCAT] N/A

[_SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DE-LED-X65-MFL
Item No.	
Manufacturer	B-K LIGHTING INC

Main Light Measurement Results

Luminaire lumens	1634 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	57.59 lm/W
Total Luminaire Watts	28.38 W
Upward Waste Light Ratio	0%
Maximum Candela	4806 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	3.802 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B2 U0 G0

IES ROAD REPORT



Light measurement results

Print date 12/19/2025

IESNA TM-15-07 LUMINIAIRE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	752.3	lm	46.04%
Medium (30-60°)	55.21	lm	3.379%
High (60-80°)	8.426	lm	0.5157%
Very High (80-90°)	1.013	lm	62.02%

Back Light

Low (0-30°)	752.3	lm	46.04%
Medium (30-60°)	55.21	lm	3.379%
High (60-80°)	8.426	lm	0.5157%
Very High (80-90°)	1.013	lm	62.02%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	1634	lm	100%
------------	-------------	-----------	-------------

BUG RATING B2 U0 G0

