

IES ROAD REPORT



Light measurement results

Print date 12/23/2025

PHOTOMETRIC FILENAME : DI-LED-TR-e150-10°-NSP

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a
[TESTLAB] UL, LLC
[MANUFAC] B-K Lighting INC
[ISSUE DATE] 12/23/2025
[LUMINAIRE] DI-LED-TR-e150-10°-NSP
[LUMCAT] N/A
[SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DI-LED-TR-e150-10°-NSP
Item No.	
Manufacturer	B-K Lighting INC

Main Light Measurement Results

Luminaire lumens	463.2 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	49.55 lm/W
Total Luminaire Watts	9.347 W
Upward Waste Light Ratio	0%
Maximum Candela	6486 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	1.586 cd
Correlated Color Temperature, CCT	2700 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	183	lm	39.4%
Medium (30-60°)	42.1	lm	9.10%
High (60-80°)	6.18	lm	1.33%
Very High (80-90°)	0.632	lm	0.137%

Back Light

Low (0-30°)	183	lm	39.4%
Medium (30-60°)	42.1	lm	9.10%
High (60-80°)	6.18	lm	1.33%
Very High (80-90°)	0.632	lm	0.137%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total			
Sum	463.2	lm	100%

BUG RATING B1 U0 G0

