

# IES ROAD REPORT

Light measurement results

**PHOTOMETRIC FILENAME : DI-LED-TR-e151-7°-VNSP**

## DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002  
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a  
[TESTLAB] UL, LLC  
[MANUFAC] B-K Lighting INC  
[ISSUE DATE] 12/23/2025  
[LUMINAIRE] DI-LED-TR-e151-7°-VNSP  
[LUMCAT] N/A  
[SERIALNUMBER] n/a - n/a

## Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

## Tested Light Source

Luminaire	DI-LED-TR-e151-7°-VNSP
Item No.	
Manufacturer	B-K Lighting INC

## Main Light Measurement Results

Luminaire lumens	460.2 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	49.54 lm/W
Total Luminaire Watts	9.291 W
Upward Waste Light Ratio	0%
Maximum Candela	14177 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	1.242 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index, CRI	80.0

## Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

# IES ROAD REPORT

## IESNA TM-15-07 LUMINIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

### Forward Light

Low (0-30°)	197	lm	42.8%
Medium (30-60°)	28.9	lm	6.28%
High (60-80°)	3.87	lm	0.841%
Very High (80-90°)	0.462	lm	0.100%

### Back Light

Low (0-30°)	197	lm	42.8%
Medium (30-60°)	28.9	lm	6.28%
High (60-80°)	3.87	lm	0.841%
Very High (80-90°)	0.462	lm	0.100%

### Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total			
<b>Sum</b>	<b>460.2</b>	<b>lm</b>	<b>100%</b>

### BUG RATING B1 U0 G0

