

IES ROAD REPORT



Light measurement results

Print date 12/29/2025

PHOTOMETRIC FILENAME : DI-LED-TR-e152-17.5°-SP

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] Viso LabSpion - serial: n/a sensor serial: n/a
[TESTLAB] UL, LLC
[MANUFAC] B-K Lighting INC
[ISSUE DATE] 12/29/2025
[LUMINAIRE] DI-LED-TR-e152-17.5°-SP
[LUMCAT] N/A
[SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	3
Tested gamma angles, qty	181

Tested Light Source

Luminaire	DI-LED-TR-e152-17.5°-SP
Item No.	
Manufacturer	B-K Lighting INC

Main Light Measurement Results

Luminaire lumens	480.9 lm
Downward Total Efficiency	100%
Total Luminaire Efficiency	100%
Luminaire Efficacy Rating (LER)	51.58 lm/W
Total Luminaire Watts	9.323 W
Upward Waste Light Ratio	0%
Maximum Candela	2973 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	2.087 cd
Correlated Color Temperature, CCT	3500 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

IES ROAD REPORT



Light measurement results

Print date 12/29/2025

IESNA TM-15-07 LUMINAIARE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	190	lm	39.5%
Medium (30-60°)	42.5	lm	8.83%
High (60-80°)	7.58	lm	1.58%
Very High (80-90°)	0.693	lm	0.144%

Back Light

Low (0-30°)	190	lm	39.5%
Medium (30-60°)	42.5	lm	8.83%
High (60-80°)	7.58	lm	1.58%
Very High (80-90°)	0.693	lm	0.144%

Uplight

Low (90-100°)	0	lm	0%
High (100-180°)	0	lm	0%

Total

Sum	480.9	lm	100%
------------	--------------	-----------	-------------

BUG RATING B1 U0 G0

