

# IES ROAD REPORT

---

**PHOTOMETRIC FILENAME : NS-LED-e204-SP-WHP-9-E**

**DESCRIPTIVE INFORMATION (From Photometric File)**

IESNA:LM-63-2002  
 [TEST] n/a serial: n/a  
 [TESTLAB] UL, LLC  
 [MANUFAC] B-K LIGHTING INC  
 [ISSUEDATE] 3/11/2026  
 [LUMINAIRE] NS-LED-e204-SP-WHP-9-E  
 [LUMCAT] N/A  
 [SERIALNUMBER] n/a - n/a

**Measurement Conditions**

Tested c-planes, qty	3
Tested gamma angles, qty	181

**Tested Light Source**

Luminaire	NS-LED-e204-SP-WHP-9-E
Item No.	
Manufacturer	B-K LIGHTING INC

**Main Light Measurement Results**

Luminaire lumens	450 lm
Downward Total Efficiency	100.0%
Total Luminaire Efficiency	100.0%
Luminaire Efficacy Rating (LER)	46.9 lm/W
Total Luminaire Watts	9.594 W
Upward Waste Light Ratio	0%
Maximum Candela	2146 cd
Maximum Candela Angle	180H 0V
Maximum Candela (<90 Degrees Vertical)	0 cd
Maximum Candela Angle (<90 Degrees Vertical)	180H 90V
Maximum Candela At 90 Degrees Vertical	0 cd
Maximum Candela from 80 to <90 Degrees Vertical	2.303 cd
Correlated Color Temperature, CCT	2700 K
Color Rendering Index, CRI	80.0

**Distribution**

IES Classification (type I,II,III,IV,V)	Type V
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Full Cutoff
BUG rating (IESNA TM-15-07)	B1 U0 G0

# IES ROAD REPORT



## IESNA TM-15-07 LUMINAIRE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

### Forward Light

Low (0-30°)	202	lm	45.0%
Medium (30-60°)	17.3	lm	3.8%
High (60-80°)	4.74	lm	1.1%
Very High (80-90°)	0.554	lm	0.1%

### Back Light

Low (0-30°)	202	lm	45.0%
Medium (30-60°)	17.3	lm	3.8%
High (60-80°)	4.74	lm	1.1%
Very High (80-90°)	0.554	lm	0.1%

### Uplight

Low (90-100°)	0	lm	0.0%
High (100-180°)	0	lm	0.0%

Total			
<b>Sum</b>	<b>450.0</b>	<b>lm</b>	<b>100,0%</b>

### BUG RATING B1 U0 G0

