

IES ROAD REPORT

PHOTOMETRIC FILENAME : NS-LED-e206-MFL-WHP-9-D

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] n/a serial: n/a
 [TESTLAB] UL, LLC
 [MANUFAC] B-K LIGHTING INC
 [ISSUEDATE] 3/11/2026
 [LUMINAIRE] NS-LED-e206-MFL-WHP-9-D
 [LUMCAT] N/A
 [SERIALNUMBER] n/a - n/a

Measurement Conditions

Tested c-planes, qty	73
Tested gamma angles, qty	181

Tested Light Source

Luminaire	NS-LED-e206-MFL-WHP-9-D
Item No.	
Manufacturer	B-K LIGHTING INC

Main Light Measurement Results

Luminaire lumens	441 lm
Downward Total Efficiency	96.6%
Total Luminaire Efficiency	100.0%
Luminaire Efficacy Rating (LER)	45.47 lm/W
Total Luminaire Watts	9.699 W
Upward Waste Light Ratio	3.399%
Maximum Candela	1215 cd
Maximum Candela Angle	230H 1V
Maximum Candela (<90 Degrees Vertical)	22.54 cd
Maximum Candela Angle (<90 Degrees Vertical)	355H 90V
Maximum Candela At 90 Degrees Vertical	22.52 cd
Maximum Candela from 80 to <90 Degrees Vertical	27.29 cd
Correlated Color Temperature, CCT	3500 K
Color Rendering Index, CRI	80.0

Distribution

IES Classification (type I,II,III,IV,V)	Type I
Longitudinal Classification (Short, Medium, Long)	Very Short
Cutoff Classification (deprecated)	Cutoff
BUG rating (IESNA TM-15-07)	B1 U1 G0

IES ROAD REPORT



IESNA TM-15-07 LUMINAIRE CLASSIFICATION SYSTEM FOR OUTDOOR LUMINAIRES

Forward Light

Low (0-30°)	205	lm	46.4%
Medium (30-60°)	39.1	lm	8.9%
High (60-80°)	23.2	lm	5.3%
Very High (80-90°)	9.11	lm	2.1%

Back Light

Low (0-30°)	140	lm	31.7%
Medium (30-60°)	8.89	lm	2.0%
High (60-80°)	1.21	lm	0.3%
Very High (80-90°)	0.114	lm	0.0%

Uplight

Low (90-100°)	6.68	lm	1.5%
High (100-180°)	8.31	lm	1.9%
Total			
Sum	441.0	lm	100,0%

BUG RATING B1 U1 G0

